

GinkGo v. 2021 complete specs.

Frame set	See further below for specifications
Group set	Shimano XT throughout 1x11 drivetrain Front brake 160 mm disc Rear brake 180 mm disc Narrow-wide 34T chainring 170 mm crank arms
Wheels	700c / 622 mm Thru axle (see frame) 32 hole rims, double walled Stainless steel spokes with brass nipples Sturdy urban tires Tubes with Presta valves
Fork	Carbon fork with tapered crown (comes in black only) 100 x 12 mm thru axle Up to 160 mm disc rotor Max tire width with mud guards is 40 mm
Also included	Black aluminium alloy seat post Saddle Mud guards Black flat aluminium alloy handlebar Comfortable grips Platform pedals

Accessories

Child seats	Single or double child seat
Panels	Custom print available upon request
Spare parts	All parts included with the frame set are available as spares

Frame set

Frame	GinkGo 6061 T6 heat treated aluminum alloy Powder coated in RAL color of your choice or our standard "traffic red" (3020) 31.6 mm seat post diameter (for 36.6 mm seat post clamp, included) BSA 73 mm BB shell Tapered 1.1/8" headtube 142 x 12 mm thru axle Up to 180 mm disc rotor Made for 622 mm wheels, max tire width with mud guards is 47 mm Can also be used with 27.5x2.1" wheels and tires
Kick stand	Aluminum alloy kick stand with replaceable feet
Steering	Stainless steel rod and fasteners
Max capacity	180 kg including rider: max 70 kg on front bed and max 25 kg on rear rack (Rear rack needs to be purchased separately)